

Figure 1

Longnecker et al.
AUS920010641US1
Universal Server Farm Mass Custom Design Tool
Page 1 of 21



Figure 2


Drawing Functions
308
Drawing Program
Output Interface
306
Drawing Program Input
Interface
304
Drawing Program
302
Output Interface
312
Conversion Unit
316
GUI User Interface
314
Web Hosting Customization Tool
310

Figure 3

Illustration of Typical Visio User Interface with Manually-Edited Drawing In Progress



Figure 4
Longnecker et al.
AUS920010641US1
Universal Server Farm Mass
Custom Design Tool
Page 3 of 21


Design Type Selection
USF Design Type
Select Design Type:
Mass Custom
Custom
Open Existing Record
Accept
Cancel
500

Figure 5A



502

Figure 5B



501

Figure 5C



506

Figure 5D


IBM USF Solution Design Tool Version: 0.9
Connectivity
Step 5 of 12
Backend Connectivity
Select from the Available Network Options
T3
None
10BaseT
10BaseT
Selection Notes:
Internet Connectivity:
10BaseT connection speed is satisfactory for external connections up to 5 T1's worth of bandwidth.
[scroll down]
Help
Cancel
Performance Info
Exit
Previous
Next
Print

50%

Figure 5E



510

Figure 5F



512

Figure 5G



514

Figure 5H



516

Figure 5I



518

Figure 5J



520

Figure 5K



522

Figure 5L


Create Document
Step 12 of 12
Budget and Planning Estimate
Budget and Planning Estimate
The following estimates are for planning purposes only. The actual prices will be prepared upon a design review of this set of requirements and will vary from the estimates shown.
One-Time Fee:
$ 0.00
Monthly Recurring Fee:
$ 0.00
(based on a 36-month contract)
522
524

Figure 5M


Create Document
Step 12 of 12
Congratulations! You are nearly finished.
IBM USF Solution Design Tool
Yes
No
Help
Previous
Next
Finish
522
526

Figure 5N


User Starts Tool
User Logs in. 601
Correct password? 602
NO
YES
Search for running copy or open copy of drawing program and hide program. 603
Toolbar displayed 604
User selects button to start wizard. 605
User progresses through wizard. 607
User finishes wizard. 608
Shared or dedicated environment? 609
Open shared environment template. 610
Open Dedicated Template. 611
Calculate space requirements. 612
Add extra blank pages (as needed). 613
Create load balancing hardware/ text for input into drawing program. 614
Create server hardware/text input for drawing program. 615
Create audit trail text for input for drawing program. 616
Create other text for input into drawing program. 617
Append backend network page for input into drawing program. 618
Append client-safe page with proprietary info removed for input into drawing program. 619
Create connection inputs for drawing program. 620
Send input to drawing program. 621
Unhide drawing program displaying drawing. 622
Stop

Figure 6



Figure 7
Longnecker et al.
AU9920010641US1
Universal Server Farm Mass Custom Design Tool
Page 19 of 21

For best results this document should be viewed in color.

IBM Global Services *Content Hosting*	Customer: EXAMPLE DESIGN	IBM Confidential	File Name: EXDESIGN.vsd	
Drawn By: ROSS STARK using USF Tool		Assumptions		REV 1.0
Created: 07/25/2001	Revised: 07/25/2001	SCALE N/A	High Level Overview	SHEET 1 of 12

Legend: 10baseT connection; 100baseT connection; 1000baseT connection; Fibre connection; RS232 connection

10000919P8 . 120503

Dispatcher Server (Qty 2)
key file == NET6MDS0.003

Hardware
*IBM RS/6000 43P Model 150
*1 x 375MHz 604e PowerPC Processor
*512 MByte main memory [2 x 256 MB DIMM]
*2 x 9 GByte Hard Disk
---[Base Operating System & BOS Mirror]
*1 x Media Bay Disk Drive Mounting Kit
*3 x 10/100 Mbps Ethernet NIC Adapters
*1 x Power Supply Connection

Software
*AIX Base Operating System (BOS) [current build]
*WebSphere Edge Server Software Package
....containing SecureWay Network Dispatcher Program

Network
A Adapter: (100BaseT) External INTERNET (100)
B Adapter: (10BaseT) WEB to DB Layer + USF Admin (300)
.....[Private Firewalled Internet Access)
C Adapter: (100BaseT) Private VLAN (200)

Web Layer Firewall Server (Qty 2)
key file == FWLN4450.001

Hardware
*Nokia IP440 Base System
*1 x Intel Processor
*1 x 256 MByte RAM main memory
*1 x 20 GByte CPCI Hard Drive
*3 x Four Port 10/100 Ethernet CPCI Interface Card
*1 x Ethernet Cable (for crossover)
*1 x Power Supply
*1 x Power Supply Connection

Software
*IPSO software (operating system & Checkpoint)
*Check Point Firewall-1 Enterprise Security Suite
... * access Control
... * Authentication
... * Encryption
... * Address Translation
... * Content Security
... * Connection Control
... * Enterprise Management

Network Connections
A Adapter: External INTERNET (100)
I Adapter: Firewall to INTERNET Connection (20)
J Adapter: Firewall Logging (19)
K Adapter: Heartbeat ()
Q Adapter: Firewall Tool Resource (18)
R Adapter: Firewall Internal VLAN (200)

Virtual Routing Redundancy Protocol is used for failover.

Data Layer Firewall Server (Qty 2)
key file == FWLN6550.001

Hardware
*Nokia IP650 Base System
*1 x Intel Processor
*1 x 256 MByte RAM main memory
*1 x 6 GByte CPCI Hard Drive
*2 x Four Port 10/100 Ethernet CPCI Interface Card
*1 x Ethernet Cable (for crossover)
*2 x Power Supply
*2 x Power Supply Connection

Software
*IPSO software (operating system & Checkpoint)
*Check Point Firewall-1 Enterprise Security Suite
... * access Control
... * Authentication
... * Encryption
... * Address Translation
... * Content Security
... * Connection Control
... * Enterprise Management

Network Connections
J Adapter: Firewall Logging (19)
K Adapter: Heartbeat ()
L Adapter: Firewall to Web B (300)
M Adapter: Firewall to Data B (500)
Q Adapter: Firewall Tool Resource (18)

Virtual Routing Redundancy Protocol is used for failover.

Figure 8A
Longnecker et al.
AUS920010641US1
Universal Server Farm Mass
Custom Design Tool
Page 20 of 21

Data Base Server MED CLUSTER (Qty 1)
shown as == DB Sun E450 CLUSTER
key file == ADBSCMS0.001

Hardware
*Sun E450 Server [Qty 2 of these servers]
*4 x 400 Mhz cpu
*3072 MByte main memory
*2 x 18 GByte Hard Disk
....[Base Operating System & BOS mirror]
*2 x 36 GByte Hard Disk [Cluster Software Usage]
....[ADSM Backup System & mirror]
*1 x 12 / 24 GByte 4mm DDS-3 Internal Tape Drive
*4 x 10/100 Mbps Ethernet NIC's using 2 Quad Cards
*2 x Power Supply Connection for E450

Disk Expansion Unit w/RAID [Qty 2 of these units]
*4 x 18 GByte Hard Disk [per unit]
*2 x Power Supply Connection for Disk Exp Unit
*Total Hard Disk Storage for client data = 8 x 18 GB
....[4 x 18 GByte available with mirroring]
***Administrative Workstation= Sun Ultra 5 w/monitor
...with Terminal Concentrator Kit for sharing
*1 x Power Supply Connection

Software
*Sun Solaris Operating System (BOS) [current build]
*Sun Cluster Software & Documentation
*Sun Veritas File System Software
*Sun Veritas Volume Manager Software
to be specified
*Other software is customer supplied software

Network Connections
B (100BaseT) WEB to DB Layer + USF Admin (300)
D (100BaseT) External BACKEND (400)
E(B) (100BaseT) Failover for Adapter (B) (300)
E(D) (100BaseT) Failover for Adapter (D) (400)

Application Server (Qty 2)
shown as == Appl RS6k 6F1
key file == ADB6MDS0.301

Hardware
*RS6000 6F1 MED APP or MED DB
*2 x 450 Mhz cpu
*4096 MByte main memory
*1 x PCI Dual Channel Ultra2 SCSI Adapter
*2 x 9 GByte Hard Disk
....[Base Operating System & BOS mirror]
*1 x 4-Channel Ultra3 SCSI PCI RAID Adapter
*6 x 18 GByte Hard Disk [client data]
....[3 x 18 GByte available with mirroring]
*4 x 10/100 Mbps Ethernet NIC's
*2 x Power Supply Connection

Software
*AIX Base Operating System (BOS) [current build]
Advanced Ed.of WebSphere Appl.Server
*Other software is customer supplied software

Network Connections
B (100BaseT) WEB to DB Layer + USF Admin (300)
D (100BaseT) External BACKEND (400)

Figure 8B
Longnecker et al.
AUS920010641US1
Universal Server Farm Mass
Custom Design Tool
Page 21 of 21

Administration Workstation
Hardware
- Sun Ultra Enterprise Ultra 10 Model 440
- 1 x 440MHz UltraSPARC-IIi
- 256MB DRAM
- 2 x 9.1GB 7200 RPM Hard Disk (EIDE)
- 1 x 17in Monitor

Software
- Solaris 2.6

Network
- A Adapter (integrated): USF Admin (Data Admin (500))

Other Hardware
- 1 x Terminal Concentrator Kit

Fail Over Scheme:
- Server 1 fails over to server #2

EXP200 Notes:

You may need to include the following parts in your EXP200 configuration:

-	03K9311	IBM Netfinity 4.2M Ultra2 SCSI Cable
-	37L5857	Netfinity EXP200 Rack-to-Tower Conversion Kit
-	37L0075	Netfinity EXP200 350W Redundant Power Supply